





MAXIVISION® CAMERA SYSTEMS

Safety and productivity for your equipment.



Cameras

The Maxi Vision® range of cameras have been specifically designed to suit the harshest of environments.

PN 14220



Features

- Sony ISX017 WDR Sensor Colour CMOS
- High Resolution 1000 TV Lines
- Low Illumination
- Rated to IP69K
- In-built Power Status LED
- On-screen Activity Indicator

BALL CAMERA IP69K HEAVY DUTY

The 14220 camera features the latest Sony CMOS technology housed in a rugged, IP69K, die-cast assembly, making this camera one of the leading vision components available.

Compact in design and lightweight, this camera reduces the amount of machine space required for fitment while providing crystal-clear imagery.

Specifications

Dims: 70 mm (2.7")(H) 53 mm (2"))D)(with bracket)Weight: 120 g (0.2 lbs) (without bracket)Operating Temp: $-20^{\circ}\text{C} \sim 60^{\circ}\text{C} (-4^{\circ}\text{F} - 140^{\circ}\text{F})$ Angle of Vision: $82 (\text{H}) \times 61 (\text{V}) \times 104 (\text{D})$ Total Pixels: $1,297 (\text{H}) \times 977 (\text{V}) 1.27 \text{M}$ Min Illumination: 0.1 Lux (F=2.0)

Input Voltage: 12 / 24 V DC

PN 11858



COLOUR CAMERA IP68 CCD HAD II (SMALL)

- Operating temp: -20°C 65°C (-4°F 149°F)
- Lens: F 2.0/30 IRE
- Min illumination: 0.5 Lux
- Input voltage: 12 V DC
- 36.6(W) x 27(H) x 37.7(D) mm (1.4" x 1" x 1.5")
- 80g (0.17lbs)
- Aluminium die-cast waterproof housing
- Complete with 20m (65.6ft) loom
- Waterproof microphone

PN 0683



BLACK & WHITE CAMERA 110°

- Operating temp: -10°C 55°C (14°F 131°F)
- Lens: F 2.0 110°
- Min illumination: 1 Lux
- Input voltage: 12 V DC
- 70(W) x 44(H) x 57(D) mm (2.7" x 1.7" x 2.2")
- 300g (0.66lbs) including bracket
- Aluminium die-cast waterproof housing
- Waterproof microphone
- Complete with 20m (65.6ft) loom





COLOUR CAMERA IP69 CCD HAD II

- Operating temp: -20°C 60°C (-4°F 140°F)
- Lens: F 2.0 110°
- Min illumination: 0.1 Lux
- Input voltage: 12 V DC
- 70(W) x 44(H) x 57(D) mm (2.7" x 1.7" x 2.2")
- 400g (0.88lbs) including bracket
- Aluminium die-cast waterproof housing
- Complete with 20m (65.6ft) loom

PN 11846



COLOUR CAMERA INFRA-RED 110°

- Visible IR LED (850nm) x6
- Input voltage: 12 V DC
- 70(W) x 44(H) x 57(D) mm (2.7" x 1.7" x 2.2")
- 400g (0.88lbs) (with bracket)
- IP67
- Built-in audio

PN 14348



DUAL VIEW CAMERA A TYPE

- Operating temp: -20°C 60°C (-4°F 140°F)
- View Angle: Drive: 80(H) x 60(V) x 95(D)
 Rear: 120(H) x 90(V) x 140(D)
- Mini illumination: 0.2 Lux (F=2.4)
- Input voltage: 12 / 24 V DC
- 28(W) x 33(D) mm (1.1" x 1.3")
- 44.5q (0.1lbs)
- IP68 metal housing

Monitors



5" WATERPROOF MONITOR COLOUR TFT IP67 HEAVY DUTY 12/24V

- Reverse polarity protected
- 3 camera input (NTSC/PAL)
- Full screen picture display
- Complete with heavy duty mounting, sun visor and all cabling
- 3 standby wire function
- 2.5m (8.2ft) sealed connection lead
- Manual dimmer function inbuilt (day/night function)



7" WATERPROOF MONITOR COLOUR TFT IP67 HEAVY DUTY 12/24V

- Reverse polarity protected
- 7 different screen layouts
- 1, 2, 3 and 4 split screen
- Complete with heavy duty mounting, sun visor and all cabling
- 4 standby wire function
- 2.5m (8.2ft) sealed connection lead
- Auto dim function for easy viewing in changing light conditions
- Internal mirror image settings
- Easy to navigate menus via on screen display (OSD)



7" MONITOR COLOUR TFT IN CAB 12/24V

- Split connections for easy installation
- Auto dim function for easy viewing in changing light conditions
- Lightweight and durable for easy handling and longer use
- Touch screen control for ease of use, also includes remote control



10.4" MONITOR COLOUR TFT LCD METAL CASE 12V

- Power consumption: 9.6W
- Operating temp: -10°C to 50°C (14°F to 122°F)
- Dims: 254(W) x 202(H) x 29(D) mm (10" x 7.9" x 1.1")
- Weight: 1.5kg (3.3lbs)
- Card type IR remote control
- Auto TV system (NTSC, PAL, AUTO)
- 0.5 W speaker @ 12V



10" W/PROOF MONITOR COLOUR TFT HEAVY DUTY 12/24V

- 1, 2, 3 and 4 split screen
- Comes with heavy duty mounting
- Stand-by wire function
- Internal mirror image settings & On Screen display (OSD)
- Auto dim function for easy viewing in changing light conditions
- Operating temp: -20°C to 60°C (-4°F to 140°F)
- Dims: 263(W) x 183(H) x 29(D) mm (10.3" x 7.2" x 1.1")
- Weight: 877g (1.9lbs)
- NTSC, PAL, AUTO
- 0.5 W speaker



7" TELEVISION LCD TFT 12V

- On Screen Display (OSD)
- 0.5 W speaker installed
- TV/AV/camera selection function
- Card type IR remote control
- Fast channel search and auto memory
- Wide range of channels (CH2-CH69)
- External antenna & AV inputs plus multiple connections
- Camera connection terminal
- Low energy consuming rate (Max power: 950mA @ 12V)



15" MONITOR COLOUR LCD TFT 12V

- On Screen Display (OSD)
- 0.5 W speaker installed
- IR remote control
- External antenna input
- External AV input and multiple connection
- Low energy consuming rate (Max power: 950mA @ 12V)
- Dims: 381(W) x 299(H) x 46(D)mm (15" x 11.7" x 1.8")
- Weight: 3.5kg (7.7lbs)
- Pixels: 1024 x 768



27" MONITOR COLOUR LCD TFT 12V

- On Screen Display (OSD)
- 0.5 W speaker installed
- Inputs: AV, HDMI, VGA, PC stereo
- Power consumption: <30W</p>
- Dims: 648.5 x 401 x 68mm (25.5" x 15.7" x 2.6")
- Weight: 7kg (15.4lbs)
- Pixels: 1920 x 1080

Accessories & Cabling

The Maxi Vision® looms and adaptors have been designed to integrate the Maxi Vision® range with current machine infrastructure.

PN 6838



Features

- Voltage in: 12 24V DC Voltage out: 12V DC 1A
- Power consumption: 200mA
- 380g (0.8lbs)

QUAD SPLITTER BOX 4 CAMERA INPUT

The Maxi Vision® Quad Splitter has been specifically designed to integrate multiple cameras into any Maxi Vision® monitor.

Including four trigger line inputs, this unit can display 1/2/3/ or 4 images on screen at the same time.

- -10°C to 60°C (14°F to 140°F)
- 140(W) x 30(H) x 90(D) mm (5.5" x 1.1" x 3.5")
- Wireless remote control
- 4 camera input, multi-screen display
- Reverse wire auto-on function on all camera inputs



CAMERA INPUT LOOM TO SUIT 11939 MONITOR

1 x Camera Input | PN 11927 2 x Camera Input | PN 11928 3 x Camera Input | PN 11929 4 x Camera Input | PN 11930



ADAPTOR KIT (MINI DIN TO DEUTSCH PLUG)

- Heavy duty four core harness
- Cable length 400mm (15.7")



REDUCER REGULATOR

- Regulates power input to absorb machine spike voltage
- Set incoming voltages 9 to 32 V DC
- Output: 12V 3 Amp



EXTENSION LOOM TO SUIT 11857 / 0683 CAMERA

5m (15ft) | PN **1346** 20m (70ft) | PN **5593**



ADAPTOR LOOM TO SUIT 11586/14220 CAMERA



ADAPTOR LOOM TO SUIT 10895 DVR SYSTEM



EXTENSION LOOM 7M TO SUIT 11858 CAMERA



ADAPTOR LOOM RCA MALE TO RCA MALE 1M



ADAPTOR LOOM
MINI DIN TO RCA INPUT



ADAPTOR KIT TO SUIT MINI JACK (SCREW TYPE) TO DEUTSCH

Mounting Kits & Enclosures

The Maxi Vision® range of mounting kits and enclosures has been designed to integrate with current machine infrastructure.

These specific mounting options have been manufactured to allow Maxi Vision® systems to be mounted in different applications and positions in and around the cab.



MOUNTING KIT TO SUIT 7205 MONITOR (RAM MOUNT)



MOUNTING KIT TO SUIT 11939 MONITOR LIGHT DUTY



ENCLOSURE TO SUIT 0683 / 11857 CAMERA



MOUNTING KIT TO SUIT 11939 / 9299 MONITOR (RAM MOUNT)



MOUNTING KIT TO SUIT 9299 MONITOR LIGHT DUTY

Maxi Vision® Ram Mounting

Maxi Vision® systems have a RAM mounting solution to suit most applications.























RAM Double Socket Arm



8795 + 8460 8795 + 8799



8494 + 8460





9292 + 8799

8494 + 8799



8455 + 8460



8455 + 8799



8493 + 8460



8798 + 8460



8798 + 8799



8492 + 8799



8492 + 8460

15475 + 8460



15475 + 8799



15475 RAM Base

8798 **RAM** Base 2" x 6" Universal Rectangular

8492 RAM Base 2.5"

Diameter Round

Digital Video Recorders (DVR)

PN 16203



Features

- IP69K waterproof
- All diecast case
- SD card cover locking system
- Wi-Fi (optional)
- Compact design
- 4-trigger wire input

Specifications

Dims: 198mm (7.8")(W)

34.5mm (1.4")(H) 100mm (4")(D)

Weight: 822g (1.8lbs)

DVR only

Compression: H.264/AVI

Memory: SD Card (Min 16GB

Max 512GB)

Normal / Event

Frame: 4 Channel (30fps)

GPS: External Microphone: External

Mode:

3G-Sensor: Internal (5 step)

RECORDER DVR 4 CHANNEL SD CARD

The Maxi Vision® Digital Video Recorder (DVR) is robust in design and ideally suited to industrial and mining applications. Housed in an aluminium casing, this IP69K recorder is designed to stand up to the harshest of environments.

Automatically recording events, 20 seconds pre and post, this multi-voltage unit comes complete with a 256GB SD Card, GPS Antenna, Remote Control and four camera inputs.

View all recorded images on-screen (four camera view including displayed GPS co-ordinates and GPS speed indicator).

Images are easily downloaded by the Maxi Vision® PC Viewer showing over speed, events, driving route, speed, time, location and GPS tracking via Google map interface (Terrain or Map display available).

This all-in-one unit is your solution for driver management, events recording, machine monitoring and training.

Time: Ordinary: Recording at intervals of 2 min.

Event: 10 seconds prior, 20 second

Current: 350mA @12VDC

Input Voltage: 12 - 24 V DC

Resolution: 4 Channel HD (TVI, AHD, CVBS)

Temp Range: Operating: -10°C to 60°C (14°F to 140°F)

Storage: -20°C to 70°C (-4°F to 158°F)

Trigger Wire: 4 Input

Record Time: (Normal Video Quality – 960 x 480).

Note: SD Card must be formatted via

supplied PC Viewer

16GB - 7H Normal, 2H 55M Event

256GB – 4D 16H Normal, 1D 22H 40M Event 512GB – 10D 17H 34M Normal, 3D 8H Event



RECORDER DVR 4 CHANNEL NO SD CARD



RECORDER DVR 2 CHANNEL NO SD CARD

PN 13542



DVR COMPACT RECORDER 2 CAMERA

The all-in-one unit solution for driver management, events recording, machine monitoring and training.

The Compact DVR Recorder has been designed to assist with in-cab and forward monitoring on mobile equipment.

This multi-voltage unit comes complete with in-built forward and reverse cameras, SD card, GPS and G-shock sensors.

Images are easily downloaded by the Maxi Vision® PC Viewer showing over speed, events, driving route, speed, time, location and GPS tracking via Google map interface (Terrain or Map display available).

Specifications

Dims: 105mm (4.1")(W)

22mm (0.8")(H)

67mm (2.6")(D)

Weight: 156g (0.34lbs) incl. bracket

Compression: H.264/AVI

Memory: SD Card

(max 64GB)

Frame: 30fps x 2 (Parking: 1fps)

G-sensor: Internal

GPS: Internal (5 step)

Mode: Ordinary / Event (Motion / G-sensor)

Time: Ordinary: Recording at intervals of 2 min.

Event: 10 seconds prior, 20 second

Current: 350mA @12VDC

Input Voltage: 12 - 24 V DC (with super cap) @max.32V

Resolution: Inside: VGA (640x480)

Outside : HD (1280x720)

Temp Range: Operating: -10°C to 60°C (14°F to 140°F)



RECORDER DVR 4 CHANNEL 256GB SD CARD



256GB SD CARD

5" Camera Kits

The Maxi Vision® camera range offers operators a new perspective when operating their equipment - enhancing safety and productivity.



5" BLACK & WHITE CAMERA KIT

Standard Camera

1 x Camera Kit	Part no. 3630
2 x Camera Kit	Part no. 3628
3 x Camera Kit	Part no. 3624

Kit includes:

1	9299	5" MONITOR LCD
1-3	0683	BLACK & WHITE CAMERA
1	3876	RED/REG 9-32V IN 12V 2A OUT



5" COLOUR CAMERA KIT

Standard Camera

1 x Camera Kit	Part no. 3648
2 x Camera Kit	Part no. 3638
3 x Camera Kit	Part no. 3617

Kit includes:

1	9299	5" MONITOR LCD
1-3	11857	COLOUR CAMERA
1	3876	RED/REG 9-32V IN 12V 2A OUT



5" COLOUR CAMERA KIT

Heavy Duty Camera

	Part no. 11688
	Part no. 11689
3 x Camera Kit	Part no. 11690
Kit includes:	

1	9299	5" MONITOR LCD
1-3	14220	COLOUR CAMERA
1-3	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)
1	3876	RED/REG 9-32V IN 12V 2A OUT
1-3	5593	EXTENSION LOOM 70FT / 20M (1 PER CAMERA)



5" COLOUR CAMERA KIT

Light Vehicles

1 x Camera Kit | Part no. 9391

(it	inc	ludes:

1	9299	5" MONITOR LCD
1	11858	COLOUR CAMERA IP68 CCD HAD II (SMALL)
1	8420	LIGHT DUTY FAN MOUNT

7" Camera Kits



7" COLOUR CAMERA KIT

Commercial Vehicle

1 x Camera Kit	PN 11931	3 x Camera Kit	PN 11933
2 x Camera Kit	PN 11932	4 x Camera Kit	PN 11934

Kit ind	cludes:	
1	11926	7" MONITOR LCD
1-4	11858	COLOUR CAMERA (SMALL)
1	11945	4 CAMERA INPUT LOOM TO SUIT 11926 MONITOR



7" BLACK & WHITE CAMERA KIT

Standard Camera

1 x Camera Kit	Part no. 4271	3 x Camera Kit	PN 8810
2 x Camera Kit	Part no. 4272	4 x Camera Kit	Part no. 8811

Kit includes:

NIL IIICII	udes.	
1	11939	7" MONITOR LCD
1-4	0683	BLACK & WHITE CAMERA
1	11927/11928 11929/11930	1/2/3/4 CAMERA INPUT LOOM TO SUIT 11939 MONITOR



7" COLOUR CAMERA KIT

Standard Camera

1 x Camera Kit	Part no. 4218	3 x Camera Kit	Part no. 4108
2 x Camera Kit	Part no. 4219	4 x Camera Kit	Part no. 8816

Kit includes:

i die ii iei	aacs.	
1	11939	7" MONITOR LCD
1-4	11857	COLOUR CAMERA
1	11927/11928 11929/11930	1/2/3/4 CAMERA INPUT LOOM TO SUIT 11939 MONITOR



7" COLOUR CAMERA KIT

Heavy Duty Camera

1 x Camera Kit	Part no. 11691	3 x Camera Kit	Part no. 11694
2 x Camera Kit	Part no. 11692	4 x Camera Kit	Part no. 11695

Kit includes:

IXIC II ICI	iuues.	
1	11939	7" MONITOR LCD
1-4	14220	COLOUR CAMERA
1	11927/11928 11929/11930	1/2/3/4 CAMERA INPUT LOOM TO SUIT 11939 MONITOR
1-4	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)
1-4	5593	EXTENSION LOOM 70FT / 20M (1 PER CAMERA)



7" COLOUR CAMERA KIT

Dual View

1 x Camera Kit | Part no. 14391

Kit ind	cludes:	
1	11926	7" MONITOR LCD
1	14348	CAMERA 1.3M MULTI VIEW
1	11942	1 CAMERA INPUT LOOM

10.4" Camera Kits



10.4" COLOUR CAMERA KIT

Standard Camera

1 x Camera Kit	PN 6221	3 x Camera Kit	PN 10965
2 x Camera Kit	PN 7746	4 x Camera Kit	PN 10966

Kit inc	ludes:	
1	11935	10.4" MONITOR LCD
1-4	11857	COLOUR CAMERA
1	3876	RED/REG 9-32V IN 12V 2A OUT
1	6838	SPLITTER BOX
1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES
1	11976	SOCKET RAM DOUBLE ARM 8"
1	11979	BASE RAM 2" X 4" BALL SIZE C
1	11977	BASE RAM 75X75MM VESA SIZE C
1	13066	RAM VESA MOUNT MOUNTING HOLE



10.4" COLOUR CAMERA KIT

Heavy Duty Camera

		Part no. 11696 Part no. 11697	3 x Camera Kit Part no. 11698 4 x Camera Kit Part no. 11699
Kit inc	ludes:		
1	11935	10.4" MONITOR LCD	
1-4	14220	COLOUR CAMERA	
1	3876	RED/REG 9-32V IN 12V	2A OUT
1	6838	SPLITTER BOX	
1	2880	ADAPTOR LOOM RCA N	MALE TO RCA MALE 1.5 METRES
1-4	4946	MAXI VISION® ADAPTO	R CABLE (1 PER CAMERA)
1-4	5593	EXTENSION LOOM 70F	T / 20M (1 PER CAMERA)
1	5893	MONITOR MOUNT	

15" Camera Kits



15" COLOUR CAMERA KIT

Standard Camera

1 x Camera Kit | PN 10967

2 x Co	ımera Kit	PN 10968	4 x Camera Kit PN 10970
Kit inc	ludes:		
1	12891	15" MONITOR LCD	
1-4	11857	COLOUR CAMERA	
1	3876	RED/REG 9-32V IN 12	V 2A OUT
1	6838	SPLITTER BOX	
1	2880	ADAPTOR LOOM RCA	MALE TO RCA MALE 1.5 METRES
1	10973	RAM ARM 8" 2.25" BAI	_L
1	10972	RAM BASE 2" X 3" 2.25	"BALL

3 x Camera Kit | PN 10969



15" COLOUR CAMERA KIT

10971 RAM BASE 75X75MM VESA MOUNT

Heavy Duty Camera

		Part no. 11701 Part no. 11702	3 x Camera Kit Part no. 11703 4 x Camera Kit Part no. 11704
Kit inc	cludes:		
1	12891	15" MONITOR LCD	
1-4	14220	COLOUR CAMERA	
1	3876	RED/REG 9-32V IN 12V 2	A OUT
1	6838	SPLITTER BOX	
1	2880	ADAPTOR LOOM RCA MA	ALE TO RCA MALE 1.5 METRES
1-4	4946	MAXI VISION® ADAPTOR	CABLE (1 PER CAMERA)
1-4	5593	EXTENSION LOOM 70FT	/ 20M (1 PER CAMERA)
1	10973	RAM ARM 8" 2.25" BALL	

27" Camera Kits



27" COLOUR CAMERA KIT

1 10972 RAM BASE 2" X 3" 2.25" BALL

10971 RAM BASE 75X75MM VESA MOUNT

Heavy Duty Camera

1 x Camera Kit	Part no. 11705	3 x Camera Kit	Part no. 11707
2 x Camera Kit	Part no. 11706	4 x Camera Kit	Part no. 11708

Kit includes:

Kit inci	uaes:	
1	12772	27" MONITOR LCD
1-4	14220	COLOUR CAMERA
1	3876	RED/REG 9-32V IN 12V 2A OUT
1	6838	SPLITTER BOX
1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES
1-4	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)
1-4	5593	EXTENSION LOOM 70FT / 20M (1 PER CAMERA)
1	10973	RAM ARM 8" 2.25" BALL
1	10972	RAM BASE 2" X 3" 2.25" BALL
1	10971	RAM BASE 75X75MM VESA MOUNT

DVR Camera Kits

The Maxi Vision® Digital Video Recorder (DVR) is robust in design and ideally suited to industrial and mining applications. Housed in an aluminium casing this recorder is designed to stand up to the harshest of environments.

This multi-voltage unit comes complete with heavy duty Solid State Drive (SSD), GPS antenna, remote control and four camera input.

View all recorded images on screen (four camera view including displayed GPS co-ordinates and GPS speed indicator).

Images are easily downloaded by the Maxi Vision® PC Viewer showing over speed, events, driving route, speed, time, location and GPS tracking via Google map interface (terrain or map display available).

This all-in-one unit is your solution for driver management, events recording, machine monitoring and training.



5" COLOUR DVR CAMERA KIT

Heavy Duty Camera

		Part no. 11713 Part no. 11714	3 x Camera Kit Part no. 11715
Kit inc	ludes:		
1	9299	5" MONITOR LCD	
1-3	14220	COLOUR CAMERA	
1	16203	RECORDER DVR 4CH SD CA	RD

1-3	14220	COLOUR CAMERA
1	16203	RECORDER DVR 4CH SD CARD
1-4	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)
1	3876	RED/REG 9-32V IN 12V 2A OUT
1-4	5593	EXTENSION LOOM 70FT / 20M (1 PER CAMERA)
1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES
1	8093	ADAPTOR CABLE MINI DIN TO RCA



7" COLOUR DVR CAMERA KIT

Standard Camera

1 x Camera Kit	Part no. 10948	3 x Camera Kit	Part no. 10950
	Part no. 10949	4 x Camera Kit	

Kit includes:

1	11939	7" MONITOR LCD
1-4	11857	COLOUR CAMERA
1	16203	RECORDER DVR 4CH SD CARD
1-4	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)
1	11927/11928 11929/11930	1/2/3/4 CAMERA INPUT LOOM TO SUIT 11939 MONITOR
1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES
1	8093	ADAPTOR CABLE MINI DIN TO RCA



7" COLOUR CAMERA KIT

Heavy Duty Camera

1 x Camera Kit	Part no. 11709	3 x Camera Kit	Part no. 11711
2 x Camera Kit	Part no. 11710	4 x Camera Kit	Part no. 11712

Cit includes

Kit includes:				
1	11939	7" MONITOR LCD		
1-4	14220	COLOUR CAMERA		
1	16203	RECORDER DVR 4CH SD CARD		
1	11927/11928 11929/11930	1/2/3/4 CAMERA INPUT LOOM TO SUIT 11939 MONITOR		
1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES		
1	8093	ADAPTOR CABLE MINI DIN TO RCA		



10.4" COLOUR DVR CAMERA KIT

Standard Camera 1 x Camera Kit | PN 10954

ZXC	amera Kit	PN 10955	4 x Camera Kit PN 10957
Kit in	cludes:		
1	11935	10.4" MONITOR LCD	
1-4	11857	COLOUR CAMERA	
1	16203	RECORDER DVR 4CH	I SD CARD
1	3876	RED/REG 9-32V IN 1	2V 2A OUT
1	2880	ADAPTOR LOOM RC	A MALE TO RCA MALE 1.5 METRES

3 x Camera Kit | PN **10956**

3 x Camera Kit | Part no. 11719



10.4" COLOUR DVR CAMERA KIT

MONITOR MOUNT

Heavy Duty Camera

1 x Camera Kit | Part no. **11717**

5893

2 x Co	ımera Kit	Part no. 11718	4 x Camera Kit Part no. 11720
Kit inc	ludes:		
1	11935	10.4" MONITOR LCD	
1-4	14220	COLOUR CAMERA	
1	16203	RECORDER DVR 4CH SI	D CARD
1	3876	RED/REG 9-32V IN 12V	2A OUT
1	6838	SPLITTER BOX	
1	2880	ADAPTOR LOOM RCA N	MALE TO RCA MALE 1.5 METRES
1-4	4946	MAXI VISION® ADAPTO	R CABLE (1 PER CAMERA)
1-4	5593	EXTENSION LOOM 70F	T / 20M (1 PER CAMERA)
1	5893	MONITOR MOUNT	



15" COLOUR DVR CAMERA KIT

Heavy Duty Camera

1 x Co 2 x Co	amera Kit amera Kit	Part no. 11721 Part no. 11722	3 x Camera Kit 4 x Camera Kit	
Kit in	cludes:			
1	12891	15" MONITOR LCD		

K	Kit includes:				
1	1	12891	15" MONITOR LCD		
1	1-4	14220	COLOUR CAMERA		
1	1	16203	RECORDER DVR 4CH SD CARD		
1	1	3876	RED/REG 9-32V IN 12V 2A OUT		
1	1	6838	SPLITTER BOX		
1	1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES		
1	1-4	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)		
1	1-4	5593	EXTENSION LOOM 70FT / 20M (1 PER CAMERA)		
1	1	10973	RAM ARM 8" 2.25" BALL		
1	1	10972	RAM BASE 2" X 3" 2.25" BALL		
1	1	10971	RAM BASE 75X75MM VESA MOUNT		



27" COLOUR DVR CAMERA KIT

Heavy Duty Camera

1 x Camera Kit	Part no. 11725	3 x Camera Kit	Part no. 11727
2 x Camera Kit	Part no. 11726	4 x Camera Kit	Part no. 11728

ιt	ınc	lua	les:	

1	12772	27" MONITOR LCD
1-4	14220	COLOUR CAMERA
1	16203	RECORDER DVR 4CH SD CARD
1	3876	RED/REG 9-32V IN 12V 2A OUT
1	6838	SPLITTER BOX
1	2880	ADAPTOR LOOM RCA MALE TO RCA MALE 1.5 METRES
1-4	4946	MAXI VISION® ADAPTOR CABLE (1 PER CAMERA)
1-4	5593	EXTENSION LOOM 70FT / 20M (1 PER CAMERA)
1	10973	RAM ARM 8" 2.25" BALL
1	10972	RAM BASE 2" X 3" 2.25" BALL
1	10971	RAM BASE 75X75MM VESA MOUNT

Forklift Camera Systems

Maxi Vision® Camera systems offer operators a new perspective on driving and operating their equipment. The camera systems are designed to enhance safety by improving the operator's vision when performing such tasks as lifting, transporting loads or reversing. The systems are suitable for use on small or large forklift trucks, battery or internal combustion models.

The Maxi Vision® range of colour LCD monitor and camera options are robust in design and are ideally suited to industrial equipment. Heavy duty casing and mounting options are also available to suit custom applications.

The camera system includes pulleys, heavy duty cabling, special mounting and fittings to enable reliable installation to most electrical and Internal Combustion forklifts.



7" FORKLIFT MAST CAMERA KIT

Camera Kit | Part no. **6660**

	Kit incl	udes:	
	1	8030	7" MONITOR LCD
	1	11858	CAMERA COLOUR IP68 CCD HAD II
	1	7352	PULLEY KIT
	1	6560	MAST CAMERA ADAPTOR LOOM
	1	6559	CAMERA LOOM 15M
	1	6554	INSULATED MOUNT
	1	6623	CABLE GRIP KIT
	1	9344	MOUNT KIT T/S FORKLIFT MONITOR



7" FORKLIFT MAST CAMERA KIT

PULLEY KIT

3 Stage Mast Closed Cab

Camera Kit | Part no. 12576

7352

Kit includes

IXIC III	liuues.		
1	11931	7" - 1 COLOUR CAMERA KIT	
1	6554	MOUNTING KIT	
1	9344	MOUNT KIT T/S FORKLIFT MONITOR	
1	6560	ADAPTOR LOOM FORK FRONT CAMERA	
1	6559	CAMERA LOOM 15M	
1	6623	CABLE GRIP KIT	



Camera System Typical Layouts


5" MONITOR SYSTEM LAYOUT
7" MONITOR SYSTEM LAYOUT
10.4" MONITOR SYSTEM LAYOUT

Camera System with DVR Typical Layouts

7" MONITOR SYSTEM WITH DVR LAYOUT













rct-global.com solutions@rct-global.com